



technical data

FIBERLAUNCH ECO

The Fiberlaunch ECO is a new development of an easy to use FO launch cable on an economic price level

It is available for all kinds of connectors and fibres (SM OS2, OM1,OM2,OM3 and OM4) up to 300m

Our Fiberlaunch ECO is a high-end product with corning fibres and HQ Connectors for high-level proficiency

To each assembled Fiberlaunch ECO we provide a measurement protocol (IL,RL)



FIBERLAUNCH ECO

SINGLEMODE

MULTIMODE

length	100m, 150m, 200m, 300m	100m, 150m, 200m, 300m
fiber	Corning SMF 28 Ultra ITU-T: G.652.D G.657.A1	Corning Infinicore OM1, OM2, OM3, OM4
wavelength	1310nm - 1650nm	850nm, 1300nm
attenuation/km	max. -0,3dB	max.-0,9dB
connector	SC, LC, E2000, FCPC - also in APC	SC, LC, ST, FCPC
attenuation/connector	IL < -0,15 dB RL UPC >50dB, APC >65dB	ILdB < 0,20dB RL >30dB
mating cycles	min. 1000 cycles	min. 1000 cycles



[purchase information](#)

FL-ECO-XXX-XX/X-X-XX/X-XXX

fiber			polish	
OS2 = SM			A = APC	
OM1 = 62,5/125				
OM2 = 50/125				
OM3 = OM3	connector B			
OM4 = OM4	FC = FC-PC			
	SC = SC			
	LC = LC			
	E2 = E2000			
	ST = ST			
	connector A			
	FC = FC-PC			
	SC = SC			
	LC = LC			
	E2 = E2000			
	ST = ST			
		length		
		100 = 100m		
		150 = 150m		
		200 = 200m		
		300 = 300m		



FIBERLAUNCH distributor of your country: